

# Technical data sheet

## Clamp clip 2056 H-foot, 3-fold, plastic pressure sleeve, FT

Item number: 1186244



Clamp clip with hammerhead foot, plastic pressure sleeve made of polypropylene. For vertical and horizontal mounting of 3 single cables on a C-profile rail. For a slot width 16–17 mm. With 1-start screw thread on pressure sleeve, universal hexagonal screw head WAF10, with slot and cross recess. Suitable for assembly indoors and outdoors. Multiple cables should be separated by double sleeves. We recommend the use of a counter-sleeve.



St

Steel

FT

Hot-dip galvanised

### Master data

|                                    |                          |
|------------------------------------|--------------------------|
| Item number                        | 1186244                  |
| Type                               | BS-H3-K-46 FT            |
| Description 1                      | Clamp clip 2056          |
| Description 2                      | triple                   |
| Manufacturer                       | OBO                      |
| Dimension                          | 40-46mm                  |
| Material                           | Steel                    |
| Surface                            | Hot-dip galvanised       |
| Surface standard                   | DIN EN ISO 1461          |
| Smallest sales unit                | 25                       |
| Unit of quantity                   | Piece                    |
| Weight                             | 19.8 kg                  |
| Weight unit                        | kg/100 pc.               |
| CO2 Footprint (GWP) Cradle-to-Gate | 0,4848 kg CO2e / 1 Piece |


# Technical data sheet

## Clamp clip 2056 H-foot, 3-fold, plastic pressure sleeve, FT

Item number: 1186244



### Dimensions



|                  |        |
|------------------|--------|
| Length           | 25 mm  |
| Width            | 51 mm  |
| Height           | 182 mm |
| Plate thickness  | 2 mm   |
| Dimension A      | 25 mm  |
| Dimension B      | 51 mm  |
| Dimension C      | 40 mm  |
| Dimension G (mm) | M8     |
| Dimension H      | 182 mm |
| Dimension L      | 72 mm  |
| Dimension t      | 2 mm   |

### Technical data

|                                                |                |
|------------------------------------------------|----------------|
| Number of cables/pipes                         | 3              |
| For pipe diameter, max.                        | 46 mm          |
| For pipe diameter, min.                        | 40 mm          |
| for rail with slot width (with interval), max. | 17 mm          |
| for rail with slot width (with interval), min. | 16 mm          |
| Thread                                         | M8             |
| Halogen-free                                   | yes            |
| Length of external dimensions                  | 40 mm          |
| Max. Tightening torque                         | 5 Nm           |
| With plastic trough                            | yes            |
| Mounting type                                  | Profile rail   |
| Slot width                                     | 10 mm          |
| Clamping range D, max.                         | 46 mm          |
| Clamping range D, min.                         | 40 mm          |
| Surface addition                               | hot galvanised |
| Material addition                              | Steel          |
| With counter-trough                            | no             |
| Material of trough                             | Plastic        |
| Material quality of trough                     | Polypropylene  |